

**ASSOCIATION OF CANADA LANDS SURVEYORS - BOARD OF EXAMINERS
WESTERN CANADIAN BOARD OF EXAMINERS FOR LAND SURVEYORS
ATLANTIC PROVINCES BOARD OF EXAMINERS FOR LAND SURVEYORS**

**SCHEDULE I / ITEM 3
ADVANCED SURVEYING**

October 2005

Notes : This examination consists of 8 questions on a total of 4 pages.

Although programmable calculators may be used, candidates must show all formulae used, the substitution of values into them, and any intermediate values to 2 more significant figures than warranted by the answer.

<u>Q. No</u>	<u>Time: 3 hours</u>	<u>Marks</u>	
		<u>Value</u>	<u>Earned</u>
1	<p>If the maximum allowable angular misclosure in a traverse of n_{β} angles is M_{β} [at 99%], determine the standard deviation, σ_{β}, of each individual angle [i.e., the average from several sets], considering that each would contribute equally to the actual misclosure m_{β}.</p>	5	
2	<p>The transfer of orientation (i.e., azimuth, from the surface to a level underground) (e.g., to a tunnel or an adit) can be done down a single shaft using a pair of plumb lines, P_1 and P_2. Two ways in which this can be done are the Weisbach or pair of adjacent triangles method and the Hause or quadrilateral method. The surface connections to P_1 and P_2 are the same but the underground connections differ between the two methods.</p> <p>Compare the two methods with respect to</p> <p>a) observables and optimal geometry, with a sketch for each method; b) computational effort; and c) advantages, disadvantages, and limitations.</p>	15	

6	<p>a) Explain why a direction observed in one set using a “single second” theodolite, e.g., a Wild T2, does not have a standard deviation of $\pm 1''$. Suggest what might be a more realistic value for sights to 500 m and inclinations up to $+30^\circ$ or down to -30° [T2: 28X, plate vial $20''/\text{div}$, index $30''/\text{div}$, micrometer $1''/\text{div}$].</p> <p>b) If a single direction has a standard deviation of σ_δ in one set, what is the standard deviation, σ_β, of the mean value of an angle, β, measured in n_s sets by the same theodolite under the same conditions [lengths and inclinations of sight]?</p> <p>c) Determine the allowable discrepancy, as would be used to check the sets in the field, between any two of the n_s sets in part b, so that the mean, β, would have the expected standard deviation, σ_β.</p>	10	
7	<p>The additive constant [or system constant or zero correction], z_0, is a correction that is applied to the output of an EODMI, $s = s' + z_0$, to account for the offset between the electronic and mechanical centres of an instrument and reflector combination. The magnitude of z_0 can be as high as 35 mm to 90 mm depending on the reflector mounting and EODMI/reflector combination.</p> <p>a) Explain how z_0 can be uniquely determined.</p> <p>b) If each distance involved in the unique determination of z_0 is ± 0.002 m, what is the consequent uncertainty in z_0?</p> <p>c) If the same EODMI as in part b is used elsewhere, say $s_i' \pm 0.002$ m, what is the uncertainty in the corrected distance, s_i?</p> <p>d) Normally corrections are expected to not significantly contribute to the uncertainty of the quantity that they are correcting. In what way could the uncertainty in z_0 be improved?</p> <p>e) i) What type of error contaminates an uncorrected distance, s', if z_0 is not applied? ii) How would that error affect the accuracy and the precision of a traverse involving n_d distances between two pairs of control points? iii) How would it affect the accuracy and the precision of a traverse involving n_d distances in a loop?</p>	15	
8	<p>A repetition instrument [theodolite or total station] can be used as a direction instrument if its lower motion remains clamped. Even so, a crusty older party chief insists that the repetition method is better than the direction method since it is faster in observing and is more precise. Consequently, he has decided to use the repetition method with the instrument even though the specifications say that the angles are to be measured as directions. Explain whether he is justified in doing so.</p>	10	
Total Marks:		100	

Percentiles of the χ^2 distribution:

	0.50	0.70	0.80	0.90	0.95	0.975	0.99	0.995
1	0.455	1.07	1.64	2.71	3.84	5.02	6.63	7.88
2	1.39	2.41	3.22	4.61	5.99	7.38	9.21	10.60
3	2.37	3.66	4.64	6.25	7.81	9.35	11.34	12.84

Some potentially useful formulae are given on the following page.

$$\tan Z = \frac{-\sin t}{\tan \delta \cos \varphi - \sin \varphi \cos t}$$

$$\sin Z = -\frac{\sin t \cos \delta}{\cos h}$$

$$\sin Z = \frac{\sin p}{\cos \varphi}$$

$$\cos Z = \frac{\sin \delta}{\cos h \cos \varphi} - \tan h \tan \varphi$$

$$-\frac{\Delta^2}{2S}$$

$$\sigma_c = \pm 0.5 \text{ mm } h; \quad \sigma_l = \pm 0.2 \text{ div}$$

$$\sigma_{\delta_c}^2 = \frac{\sigma_{c_{AT}}^2 + \sigma_{c_{TO}}^2}{s^2}; \quad \sigma_{\delta_l}^2 = \sigma_l^2 \tan^2 v$$

$$\sigma_{\delta_p}^2 = \frac{1}{2} \left[\pm \frac{45''}{M} \right]^2; \quad \sigma_{\delta_r}^2 = \frac{1}{2} [\pm 2.5'' \text{ div}]^2$$

$$\sigma_{\beta_c}^2 = \frac{\sigma_{c_{FROM}}^2}{s_{FROM}^2} + \frac{\sigma_{c_{TO}}^2}{s_{TO}^2} + \left[\frac{1}{s_{FROM}^2} + \frac{1}{s_{TO}^2} - \frac{\cos \beta}{s_{FROM} s_{TO}} \right] \sigma_{c_{AT}}^2$$

$$\sigma_{\beta_l}^2 = \sigma_l^2 [\tan^2 v_{FROM} + \tan^2 v_{TO}]$$

$$\sigma_{\beta_p}^2 = \left[\pm \frac{45''}{M} \right]^2; \quad \sigma_{\beta_r}^2 = [\pm 2.5'' \text{ div}]^2$$

$$\sigma_{\beta_{rep}}^2 = \frac{2\sigma_s^2}{n^2} + \frac{2\sigma_p^2}{n}; \quad \sigma_{\beta_{dir}}^2 = \frac{2\sigma_s^2}{n} + \frac{2\sigma_p^2}{n}$$

$$\sin \beta_1 = \frac{b_1 \sin \alpha_1}{a}; \quad \sin \beta_2 = \frac{b_2 \sin \alpha_2}{a}$$

$$\sigma_{\beta}^2 = \frac{\tan^2 \beta}{b^2} \sigma_b^2 + \frac{\tan^2 \beta}{a^2} \sigma_a^2 + \left(\frac{b^2}{a^2 \cos^2 \beta} - \tan^2 \beta \right) \sigma_{\alpha}^2$$