

CANADIAN BOARD OF EXAMINERS FOR PROFESSIONAL SURVEYORS

E5 - ADVANCED PHOTOGRAMMETRY

October 2012

Although programmable calculators may be used, candidates must show all formulae used, the substitution of values into them, and any intermediate values to 2 more significant figures than warranted by the answer. Otherwise, full marks may not be awarded even though the answer is numerically correct.

Note: This examination consists of 11 questions on 2 pages.

Marks

<u>Q. No</u>	<u>Time: 3 hours</u>	<u>Value</u>	<u>Earned</u>
1.	a) What is the objective of image matching?	2	
	b) What is the conceptual basis of the cross-correlation-based image matching?	3	
	c) What is meant by image resampling according to epipolar geometry? How would this process facilitate the image matching procedure?	3	
2.	a) What are the differences between direct and indirect transformation during image rectification? Tabulate the advantages and disadvantages of each method.	4	
	b) What is meant by the double mapping problem when generating orthophotos from large scale imagery over urban areas?	3	
	c) Explain the conceptual basis of the z-buffer method for true orthophoto generation.	3	
3.	a) What is the main limitation of a digital frame camera when compared with an analogue one?	2	
	b) What are the different alternatives for stereo-coverage using line cameras?	3	
	c) How would the stereo-coverage alternatives associated with line cameras affect the Ground Sampling Distance (GSD) in the acquired scenes?	3	
4.	a) What are the main components of an airborne LiDAR mapping system?	2	
	b) What are the main factors affecting the size of the laser footprint?	3	
	c) What is the conceptual basis of point positioning using a LiDAR system?	3	
	d) What are the main advantages of LiDAR when compared to a photogrammetric system?	3	
	e) What are the main advantages of a photogrammetric system when compared to LiDAR?	3	
	f) How would you compare the intensity image generated from a LiDAR system to an optical image?	2	
5.	a) What is the fundamental challenge in multi-sensor photogrammetric triangulation involving imagery captured by frame and line cameras onboard aerial and satellite imaging systems? Why? How would you mitigate such a challenge?	3.5	
	b) What are the main differences between the following bundle adjustment procedures: i. Photogrammetric triangulation through indirect geo-referencing, ii. GPS-controlled photogrammetric triangulation, and iii. GPS/INS-controlled photogrammetric triangulation?	4.5	
6.	a) What is the underlying assumption for using a projective transformation to relate the image and object space coordinates?	2	
	b) Briefly explain the conceptual basis for using the Rational Functional Model to relate the image and object space coordinates?	2	
	c) What are the main differences between the collinearity equation and Direct Linear Transformation models?	2	

7.	a) What are the quantities measured by a GPS/INS system onboard an imaging platform? What are the main requirements for relating these measurements to the exterior orientation of the exposure stations?	4	
	b) Can you carry out a photogrammetric reconstruction of a GPS-aided photogrammetric triangulation of a single flight line without any ground control points? Why?	2	
	c) What is meant by the following specifications and their typical values for commercial airborne LiDAR systems: <ul style="list-style-type: none"> i. Scan rate/frequency, ii. Pulse rate/frequency, iii. Ground spacing, and iv. Beam divergence? 	4	
8.	a) What is the conceptual basis for evaluating the relative accuracy of LiDAR data? What would be the main challenge in this procedure? How would you mitigate such a challenge?	5	
	b) What is the conceptual basis for evaluating the absolute accuracy of LiDAR data? What would be the main challenge in this procedure? How would you mitigate such a challenge?	4	
9.	a) For a photogrammetric system, the horizontal accuracy is superior to the vertical accuracy. Do you agree with this statement? Why?	2	
	b) For a LiDAR system, the vertical accuracy is superior to the horizontal accuracy. Do you agree with this statement? Why?	2	
	c) What are the systematic errors that might be present in a LiDAR system? How can you mitigate the impact of these errors?	3	
	d) What are the factors that would affect the inter-point spacing for LiDAR data?	3	
10.	a) What is meant by Quality Assurance (QA) and Quality Control (QC)?	2	
	b) What are the factors that should be considered in the QA for a photogrammetric mapping mission?	4	
	c) What are the QC measures for evaluating the outcome from a photogrammetric mapping mission?	2	
11.	a) What is the role of the Interior Orientation (IO) in the photogrammetric reconstruction procedure?	2	
	b) What is the role of the geo-referencing in the photogrammetric reconstruction procedure?	2	
	c) Which one of the following points (i.e., the center of the given windows) can be considered as an interest point? Why? <div style="display: flex; justify-content: space-around; margin-top: 10px;"> <div style="text-align: center;"> <p>95 94 84</p> <p>86 27 96</p> <p>100 97 87</p> </div> <div style="text-align: center;"> <p>or</p> <p>23 94 84</p> <p>34 27 96</p> <p>36 22 25</p> </div> </div>	3	
Total Marks:		100	