

**ASSOCIATION OF CANADA LANDS SURVEYORS - BOARD OF EXAMINERS
WESTERN CANADIAN BOARD OF EXAMINERS FOR LAND SURVEYORS
ATLANTIC PROVINCES BOARD OF EXAMINERS FOR LAND SURVEYORS**

SCHEDULE I / ITEM 4

September 2002

REMOTE SENSING & APPLIED PHOTOGRAMMETRY

Note: This examination consists of 11 questions on 2 pages.

Marks

<u>Q.No</u>	<u>Time: 3 hours</u>	<u>Value</u>	<u>Earned</u>
1.	Briefly explain the following terms: a) Atmospheric window b) Spectral Reflectance c) Spatial resolution d) SLAR e) False-color composite f) Image enhancement g) Radiometric calibration	14	
2.	What are the factors involved in remote sensing image acquisition that affect the image geometry?	4	
3.	a) What is a high pass filter used for? b) What is a principal component analysis (PCA) used for? c) Explain the main differences between the TM sensor on the LANDSAT and the HRV sensor onboard the SPOT satellite.	10	
4.	a) Briefly explain the following terms: • Registration • Rectification • Geocoding • Orthorectification b) Briefly describe the necessary steps and needed information for rectifying a SPOT image?	10	
5.	a) What are the major steps for the thematic classification of satellite imagery? b) What is the meaning of <i>training the classifier</i> ? c) What are the major differences between <i>supervised and unsupervised training of the classifiers</i> ? d) What is the main difference between parametric and nonparametric thematic classification of remote sensing data?	12	

6.	<p>(a) A pushbroom (linear) digital camera has 1000 array of CCD elements at a pixel size of 10 μm x 10 μm. The nominal focal length of the camera is 25 mm. What is the field of view for this camera? What will be the pixel size on the ground if the flying height is 1000m?</p> <p>(b) For a particular photograph, the measured x and y fiducials distances were 233.2 and 233.7 mm. The corresponding x and y-calibrated distances were 232.408 and 232.852 mm, respectively. Compute the corrected values for a point with photo coordinate of x = 102.9 mm and y = -92.1 mm.</p>	5	
7.	<p>The ground distance of a straight boundary of a cornfield is 550 m. The field is nearly level and lies beside the principal point of the photo. The distance on the photo of this boundary is 5.15 cm.</p> <p>a. What is the scale of the photograph?</p> <p>b. Express this scale in unit equivalents in centimeter per kilometer.</p> <p>c. If the focal length of the camera used to take the photograph is 152 mm, how high was the aircraft above the ground when taking the photograph?</p>	6	
8.	<p>What are the theoretical minimum numbers and types of control points required for the absolute orientation of aerial stereopairs? Explain your answer. What considerations are relevant to the placement of these control points? Use diagrams to illustrate your answer?</p>	10	
9.	<p>What are the conditions that are required to produce the following set of reduced collinearity equations?</p> $\left. \begin{aligned} x_a &= -f \cdot \frac{(Y_A - Y_0)}{(Z_A - Z_0)} \\ y_a &= -f \cdot \frac{-(X_A - X_0)}{(Z_A - Z_0)} \end{aligned} \right\}$	4	
10.	<p>How many 1:10,000 aerial photographs would be required to give a complete stereo coverage of a rectangular project area 15 km long by 20 km wide? For this project, you are using a standard aerial camera with a focal length of 152 mm and a 230 by 230 mm format. The forward overlap is specified as 60% and the sidelap is specified as 30%.</p>	10	
11.	<p>a) Briefly describe the principle of the Analytical Bundle Adjustment method (i.e. what is the mathematical being used, known and unknown quantities, etc.)</p> <p>b) Briefly describe the benefits of the Global Positioning System (GPS) and Inertial Navigation Systems (INS) to aerial-triangulation.</p>	10	
Total Marks:		100	0